



Solid, simple and smart:  
advanced reliability in compressed air

FONOCOMPACT PRO 1.5-7.5 kW/2-10 hp



# FONOCOMPACT PRO: your work floor companion

The Ceccato FONOCOMPACT PRO combines performance with comfort like no other piston compressor. Ultra-quiet and easy to use, the FONOCOMPACT PRO gives you reliable and powerful pneumatic support right on your work floor. With a power range from 2 to 10 hp, and flexible options for air storage and treatment, a FONOCOMPACT PRO model is always available to fit your needs.




### Extra quiet

Optimized canopy design minimizes sound levels.



### Easy to use

Intuitive control panel with pressure gauge and hour counter.



### Compact

All-in-one design reduces the unit's footprint.



### The integrated quality air solution

If you need dry, high-quality air, the FONOCOMPACT PRO series is available with an integrated refrigerant dryer for a compact all-in-one solution.



# A flexible go-getter

## Strong performance

The FONOCOMPACT PRO packs a punch in a small frame. Its new pump was designed to give you a strong, energy-efficient performance and superior reliability. A dedicated cooling fan ensures smooth operation, even in hot and dusty conditions.



## Flexible storage

To ensure stable air delivery, the FONOCOMPACT PRO offers a range of air storage options. For those with limited space, the floor-mounted unit comes with an integrated 27-liter air vessel. If you need more storage, tank-mounted models are available with 270-liter or 500-liter vessels.

## Always dependable

When you have things to do, you can't afford your compressor to break down. The FONOCOMPACT PRO's high-efficiency piston pump with low rotation speed delivers exceptional reliability and a long lifetime.



## The right FONOCOMPACT PRO to meet your needs

### FONOCOMPACT PRO 27 F2 - 27 F3

**2-3 hp / 1.5-2.2 kW**

- Extra quiet for comfortable work floor operation.
- Easy to operate and maintain.
- Integrated 27-liter air vessel ensures a stable air supply.
- Built for safety with fire-proof insulating foam and metal belt guard.
- Ideal for small pneumatic jobs.

### FONOCOMPACT PRO 100 F3 / FONOCOMPACT PRO 500 F5

**3-5.5 hp / 2.2-4 kW**

- New NS31 pump delivers increased performance and reliability.
- Canopy was designed specifically to minimize sound.
- Available in floor-mounted and tank-mounted (270 and 500-liter) models.
- All-in-one design reduces the unit's footprint.
- Ideal for automotive service stations.

### FONOCOMPACT PRO F6 / FONOCOMPACT PRO 500 F10

**5.5-10 hp / 4-7.5 kW**

- Flexible air storage options with floor-mounted and tank-mounted (270 and 500-liter) models.
- Heavy-duty cooling system with dedicated fan for dependable operation in all conditions.
- Can be outfitted with integrated dryer for an all-in-one quality air solution.
- Ideal for workshops and carpentry shops.



Extra quiet



Compact



Easy to use



Integrated vessel



Improved reliability

## FONOCOMPACT PRO 27 F2 - 27 F3 2-3 hp

Description	Power		Pressure	Pump	Pump RPM	Air displacement		Vessel	Noise	Voltage	Dimensions	Weight	Start	Outlet
	HP	KW	bar	Type	Min <sup>-1</sup>	l/min	m <sup>3</sup> /h	L.	Lp(4m)	V / ph / Hz	L x W x H	KG	DOL/YD	Connection
FONOCOMPACT PRO 27 F2SM	2	1.5	10	NS12S	1075	255	15.3	27	61	230/1/50	797x457x845	86	DOL	1/4"G
FONOCOMPACT PRO 27 F2S	2	1.5	10	NS12S	1075	255	15.3	27	61	400/3/50	797x457x845	86	DOL	1/4"G
FONOCOMPACT PRO 27 F3SM	3	2.2	10	NS12S	1350	320	19.2	27	62	230/1/50	797x457x845	87	DOL	1/4"G
FONOCOMPACT PRO 27 F3S	3	2.2	10	NS12S	1350	320	19.2	27	62	400/3/50	797x457x845	87	DOL	1/4"G



High performance



Extra quiet



Flexible storage



Compact



Improved reliability

## FONOCOMPACT PRO 100 F3 / FONOCOMPACT PRO 500 F5 3-5.5HP

Description	Power		Pressure	Pump	Pump RPM	Air displacement		Vessel	Noise	Voltage	Dimensions	Weight	Start	Outlet
	HP	KW	bar	Type	Min <sup>-1</sup>	l/min	m <sup>3</sup> /h	L.	Lp(4m)	V / ph / Hz	L x W x H	KG	DOL/YD	Connection
FONOCOMPACT PRO 100 F3SM	3	2.2	10	NS19S	1050	393	23.6	100	65	230/1/50	1002x1227x580	123	DOL	1/2" G
FONOCOMPACT PRO 100 F3S	3	2.2	10	NS19S	1050	393	23.6	100	65	400/3/50	1002x1227x580	123	DOL	1/2" G
FONOCOMPACT PRO 270s F3SM	3	2.2	10	NS19S	1050	393	23.6	270	65	230/1/50	1522x580x1242	167	DOL	1/2" G
FONOCOMPACT PRO 270s F3S	3	2.2	10	NS19S	1050	393	23.6	270	65	400/3/50	1522x580x1242	167	DOL	1/2" G
FONOCOMPACT PRO 270 F3SM	3	2.2	11	NS31	1050	444	26.6	270	65	230/1/50	1522x580x1242	175	DOL	1/2" G
FONOCOMPACT PRO 270 F3S	3	2.2	11	NS31	1050	444	26.6	270	65	400/3/50	1522x580x1242	175	DOL	1/2" G
FONOCOMPACT PRO F4S	4	3	11	NS31	1300	553	33.2	0	69	400/3/50	750x580x710	112	DOL	3/4" G
FONOCOMPACT PRO 270 F4S	4	3	11	NS31	1300	553	33.2	270	69	400/3/50	1522x580x1242	176	DOL	1/2" G
FONOCOMPACT PRO F5S	5.5	4	11	NS31	1400	598	35.9	0	69	400/3/50	750x580x710	113	DOL	3/4" G
FONOCOMPACT PRO 270 F5S	5.5	4	11	NS31	1400	598	35.9	270	69	400/3/50	1522x580x1242	177	DOL	1/2" G
FONOCOMPACT PRO 500 F5S	5.5	4	11	NS31	1400	598	35.9	500	69	400/3/50	1937x600x1348	217	DOL	3/4" G



High performance



Extra quiet



Flexible storage



Compact



Quality air

## FONOCOMPACT PRO F6 / FONOCOMPACT PRO 500 F10 5.5-10 hp

Description	Power		Pressure	Pump	Pump RPM	Air displacement		Vessel	Noise	Voltage	Dimensions	Weight	Start	Outlet
	HP	kW	bar	Type	Min <sup>-1</sup>	l/min	m <sup>3</sup> /h	L.	Lp(4m)	V / ph / Hz	L x W x H	KG	DOL/YD	Connection
FONOCOMPACT PRO F6S	5.5	4	11	NS39	1010	660	39.6	0	65	400/3/50	1045x741x955	153	DOL	3/4" G
FONOCOMPACT PRO F6XS	5.5	4	11	NS39	1010	660	39.6	0	65	400/3/50	1045x741x955	157	YD	3/4" G
FONOCOMPACT PRO 270 F6S	5.5	4	11	NS39	1010	660	39.6	270	65	400/3/50	1517x741x1487	220	DOL	1/2" G
FONOCOMPACT PRO 270 F6XS	5.5	4	11	NS39	1010	660	39.6	270	65	400/3/50	1517x741x1487	224	YD	1/2" G
FONOCOMPACT PRO 500 F6S	5.5	4	11	NS39	1010	660	39.6	500	65	400/3/50	1943x741x1593	253	DOL	3/4" G
FONOCOMPACT PRO 500 F6XS	5.5	4	11	NS39	1010	660	39.6	500	65	400/3/50	1943x741x1593	257	YD	3/4" G
FONOCOMPACT PRO 500 F6SE	5.5	4	11	NS39	1010	660	39.6	500	65	400/3/50	1943x767x1596	265	DOL	3/4" G
FONOCOMPACT PRO 500 F6XSE	5.5	4	11	NS39	1010	660	39.6	500	65	400/3/50	1943x767x1596	269	YD	3/4" G
FONOCOMPACT PRO F8S	7.5	5.5	11	NS39	1140	750	45.0	0	68	400/3/50	1045x741x955	229	DOL	3/4" G
FONOCOMPACT PRO F8XS	7.5	5.5	11	NS39	1140	750	45.0	0	68	400/3/50	1045x741x955	235	YD	3/4" G
FONOCOMPACT PRO 500 F8S	7.5	5.5	11	NS39	1140	750	45.0	500	68	400/3/50	1943x741x1593	355	DOL	3/4" G
FONOCOMPACT PRO 500 F8XS	7.5	5.5	11	NS39	1140	750	45.0	500	68	400/3/50	1943x741x1593	361	YD	3/4" G
FONOCOMPACT PRO 500 F8SE	7.5	5.5	11	NS39	1140	750	45.0	500	68	400/3/50	1943x767x1596	367	DOL	3/4" G
FONOCOMPACT PRO 500 F8XSE	7.5	5.5	11	NS39	1140	750	45.0	500	68	400/3/50	1943x767x1596	371	YD	3/4" G
FONOCOMPACT PRO F10S	10	7.5	11	NS59	810	1020	61.2	0	66	400/3/50	1045x741x955	248	DOL	3/4" G
FONOCOMPACT PRO F10XS	10	7.5	11	NS59	810	1020	61.2	0	66	400/3/50	1045x741x955	254	YD	3/4" G
FONOCOMPACT PRO 500 F10S	10	7.5	11	NS59	810	1020	61.2	500	66	400/3/50	1943x741x1593	393	DOL	3/4" G
FONOCOMPACT PRO 500 F10XS	10	7.5	11	NS59	810	1020	61.2	500	66	400/3/50	1943x741x1593	399	YD	3/4" G
FONOCOMPACT PRO 500 F10SE	10	7.5	11	NS59	810	1020	61.2	500	66	400/3/50	1943x767x1596	411	DOL	3/4" G
FONOCOMPACT PRO 500 F10XSE	10	7.5	11	NS59	810	1020	61.2	500	66	400/3/50	1943x767x1596	415	YD	3/4" G

X = star-delta start

E = intergated dryer



Contact your local representative:

[www.ceccato.com](http://www.ceccato.com)

6999100540



#### CARE

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

#### TRUST

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

#### EFFICIENCY

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.